



REINFORCED PALM



COMFORT



SMARTSWIPE™

DEMOLITION GLOVES



FEATURES

- ARMORTEX™ reinforced palms and finger tips: Increased durability and hand protection.
- SMARTSWIPE™ Knuckle: Capacitive knuckle allows to use touch screen devices without removing gloves or using dirty fingertips.
- Breathable tri-cot lining: Provides ultimate comfort and breathability.
- Knuckle protection: TPR pad provides knuckle protection.
- Terry cloth thumb: Built in sweat/brow wipe.
- Hook & Loop closure for secure fit.
- European Certified: CE Category 2, EN ISO 21420 and EN 388 (2121X).

TECHNICAL INFORMATION

COLOR OF THE GLOVE:
BLACK, GREY, RED

MATERIAL:
PALM: SYNTHETIC LEATHER. BACK: NYLON KNITTED FABRIC. KNUCKLE: TPR

SIZE RANGE:
DEMOLITION GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

UNIT GUIDE

SIZE	PACK QUANTITY	ARTICLE NUMBER
7 / S	1	4932479730
8 / M	1	48229731
9 / L	1	48229732
10 / XL	1	48229733
11 / XXL	1	48229734



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



REINFORCED PALM



COMFORT



SMARTWIPE™



DEMOLITION GLOVES

CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,
MAXIMUM WASHING
TEMPERATURE 40° CELSIUS



NO CHEMICAL
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER



5x MAX. 5 WASHING
CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



STAY **SAFE.**
STAY **PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu